

Tohatsu Four-Stroke Engines

We supply Tohatsu's Four Stroke larger 9.9, 15 and 18hp models and the 25 & 30hp. These are available with power tilt. With the new sleek streamline appearance, dependable engineering and operational ease that Tohatsu have always been known for, you'll be the envy of other four stroke users.

As well as being good looking, these new engines offer great performance together with all the features you would expect from Tohatsu outboards. Additionally, these new Four Stroke engines are as environmentally friendly as any outboard on the market; with Tohatsu's unique reduced exhaust emissions you can rest assured that your engine will pass the most stringent of emission requirements with ease.

9.9hp Model



| | |
|----------------------------------|---------------------------------|
| Engine: | 2-Cylinder |
| Displacement: | 328cc |
| Bore & Stroke: | 59 x 60 mm |
| Starting: | Electric or Manual |
| Controls: | Remote Control or Tiller Handle |
| Gear Shift: | Forward-Neutral-Reverse |
| Gear Ratio: | 2.15:1 |
| Propeller Pitch Range: | 6"-10" |
| Transom Height: | 15", 20" |
| Fuel Mix: | Wet sump |
| Fuel Tank: | 12 Litre Separate Tank |
| Weight: (Minimum Version) | 52 kgs |
| Lighting: | Optional 12V 130W 11A |
| RPM Range: | 4,500-5,500 |

Loop Charged Induction
CD Ignition System
Stainless Steel Water Pump Housing
Start-in-Gear Protection
Thermostatically Controlled Cooling System
Through-the-Prop Exhaust

Dual Swirl Combustion Chamber Heads
Shallow Water Drive
Auto-By-Starter System
Oil Pressure Indicator

15hp Model



| | |
|----------------------------------|---------------------------------|
| Engine: | 2-Cylinder |
| Displacement: | 328cc |
| Bore & Stroke: | 59 x 60 mm |
| Starting: | Electric or Manual |
| Controls: | Remote Control or Tiller Handle |
| Gear Shift: | Forward-Neutral-Reverse |
| Gear Ratio: | 2.15:1 |
| Propeller Pitch Range: | 6"-10" |
| Transom Height: | 15", 20" |
| Fuel Mix: | Wet sump |
| Fuel Tank: | 12 Litre Separate Tank |
| Weight: (Minimum Version) | 52 kgs |
| Lighting: | Optional 12V 130W 11A |
| RPM Range: | 5,000-6,000 |

Loop Charged Induction
CD Ignition System
Stainless Steel Water Pump Housing
Start-in-Gear Protection
Thermostatically Controlled Cooling System
Through-the-Prop Exhaust
Dual Swirl Combustion Chamber Heads
Shallow Water Drive
Auto-By-Starter System
Oil Pressure Indicator

18hp Model



| | |
|----------------------------------|---------------------------------|
| Engine: | 2-Cylinder |
| Displacement: | 328cc |
| Bore & Stroke: | 59 x 60 mm |
| Starting: | Electric or Manual |
| Controls: | Remote Control or Tiller Handle |
| Gear Shift: | Forward-Neutral-Reverse |
| Gear Ratio: | 2.15:1 |
| Propeller Pitch Range: | 6"-10" |
| Transom Height: | 15", 20" |
| Fuel Mix: | Wet sump |
| Fuel Tank: | 12 Litre Separate Tank |
| Weight: (Minimum Version) | 52 kgs |
| Lighting: | Optional 12V 130W 11A |
| RPM Range: | 5,000-6,000 |

Loop Charged Induction
CD Ignition System
Stainless Steel Water Pump Housing
Start-in-Gear Protection
Thermostatically Controlled Cooling System
Through-the-Prop Exhaust
Dual Swirl Combustion Chamber Heads
Shallow Water Drive
Auto-By-Starter System
Oil Pressure Indicator

25hp Model



| | |
|----------------------------------|---------------------------------|
| Engine: | 3-Cylinder |
| Displacement: | 492cc |
| Bore & Stroke: | 59 x 60mm (2.32 X 2.36 in.) |
| Starting: | Electric or Manual |
| Controls: | Remote Control or Tiller Handle |
| Gear Shift: | Forward-Neutral-Reverse |
| Gear Ratio: | 1.92:1 |
| Propeller Pitch Range: | 8"-14" |
| Transom Height: | 15", 20", 25" |
| Fuel Mix: | Wet-sump |
| Fuel Tank: | Standard 25Litre Separate Tank |
| Weight: (Minimum Version) | 68.5 kgs |
| Lighting: | 12V 180W 15A |
| RPM Range: | 5,000-6,000 |

Loop Charged Induction
CD Ignition System
Stainless Steel Water Pump Housing
Start-in-Gear Protection
Thermostatically Controlled Cooling System
Through-the-Prop Exhaust
Dual Swirl Combustion Chamber Heads
Shallow Water Drive (optional)
Auto-By-Starter System
Oil Pressure Sensor

30hp Model



| | |
|----------------------------------|---------------------------------|
| Engine: | 3-Cylinder |
| Displacement: | 492cc |
| Bore & Stroke: | 59 x 60mm (2.32 X 2.36 in.) |
| Starting: | Electric or Manual |
| Controls: | Remote Control or Tiller Handle |
| Gear Shift: | Forward-Neutral-Reverse |
| Gear Ratio: | 1.92: 1 |
| Propeller Pitch Range: | 8"-14" |
| Transom Height: | 15", 20", 25" |
| Fuel Mix: | Wet-sump |
| Fuel Tank: | Standard 25Litre Separate Tank |
| Weight: (Minimum Version) | 68.5 kgs |
| Lighting: | 12V 180W 15A |
| RPM Range: | 5,000-6,000 |

Loop Charged Induction
CD Ignition System
Stainless Steel Water Pump Housing
Start-in-Gear Protection
Thermostatically Controlled Cooling System
Through-the-Prop Exhaust
Dual Swirl Combustion Chamber Heads
Shallow Water Drive (optional)
Auto-By-Starter System
Oil Pressure Sensor

Contact Details:

Paul Richards - Cap Ferret Sports Cruisers

Web: www.capferret-sportscruisers.co.uk

E-Mail: paul@capferret-sportscruisers.co.uk

Free Phone: 0800-0192644